

SECOM 777_{TCE}



Windows CE controller for discontinuous dyeing processes

Simplest operation, outstanding efficiency and a high degree of security – that's the unique operation concept of the SECOM 777_{TCE}. The resistive touch screen allows an interactive operation – direct and straightforward. Based on Windows CE.net the SECOM 777_{TCE} is maintenance-free due to its fanless technology and is therefore the ideal choice for a long term industrial operation.

With the modular I/O concept, a performance and cost effective adaptation to all kinds of dyeing machines can be realized, according to the complexity of today's yarn, piece or other types of dyeing machines.

The SECOM 777_{TCE} with integrated PLC is used together with a decentral In-/Output System (FMD modules).




▶ SECOM 777_{TCE}

▶ Application

- Automation of all discontinuous program controlled processes in a dyehouse

▶ Application example



Specification

Hardware:

Mass-storage-system: industrial CF card

Display:

10.4" TFT color display

Resolution: 640 x 480 Pixel

Functions:

Each step: 1 main/12 parallel with
6 function parameters each

Number of functions: 200 out of 1000

Programs: max. 9999

Interfaces:

RJ45: Ethernet, 10/100 MBit
(OrgaTEX.MES)

Arcnet: SETEX PLC

USB: 2 x USB (front, rear)

Integrated UPS:

Power loss protection for minimum 10 sec

Input voltage:

Nominal voltage: 24 V DC

Range permitted: 18–36 V DC

Power consumption:

Operation: 22 VA

Inrush current: up to 10 A for max. 5 ms

Protection system:

Front: IP 54

Rear: IP 22

Ambient temperature:

Operation: 0–50 °C (32–122 °F)

Storage: 0–70 °C (32–158 °F)

Relative humidity: 15–95% no condensation

The unit is built in conformity with the following standards:

Emitted Interference: DIN EN 55022

DIN EN 61000-6-4

Interference resistance: DIN EN 61000-6-2

Security: DIN EN 60950-1


Dimensions (W x H x D):

350 x 262 x 115 mm (without connector)

Weight: approx. 4450 g



▶ Bottom view SECOM 777TCE



▶ Panel cut out: 325 x 236 mm (W x H)

▶ Depth: 111 mm (without connector)

Scope of delivery

Art. no. STS39001

1 Controller SECOM 777TCE

incl. connecting devices and mounting devices

Accessories

Art. no. BGS38550

1 Touch screen protector foil

SETEX

SETEX Schermuly textile computer GmbH
Hauptstraße 23-25 · 35794 Mengerskirchen · Germany
Tel. +49 6476 9147-0 · Fax +49 6476 9147-31
info@setex-germany.com · www.setex-germany.com